

2225-4L

3.5 Watts, 24 Volts, Class C Microwave 2200-2500 MHz

GENERAL DESCRIPTION

The 2225-4L is a COMMON BASE transistor capable of providing 3.5 Watts, Class C output power over the band 2200-2500 MHz. The transistor includes input prematching for full broadband capability. Gold metalization and diffused ballasting are used to provide high reliability and supreme ruggedness. The transistor uses a fully hermetic High Temperature Solder Sealed package.

ABSOLUTE MAXIMUM RATINGS


Maximum Power Dissipation @ 25°C 10 Watts

Maximum Voltage and Current

BVcesCollector to Emitter Voltage40 VoltsBVeboEmitter to Base Voltage3.5 VoltsIcCollector Current0.6 Amps

Maximum Temperatures

Storage Temperature $-65 \text{ to} + 200^{\circ}\text{C}$ Operating Junction Temperature $+200^{\circ}\text{C}$ CASE OUTLINE 55LV, STYLE 1



ELECTRICAL CHARACTERISTICS @ 25 °C


SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout Pin Pg	Power Out Power Input Power Gain Efficiency	F = 2200-2500 MHz Vcc = 24 Volts	3.5 8.5	40	0.5	Watts Watts dB %
ηc VSWR	Load Mismatch Tolerance	Pout =3.5Watts		.0	10:1	,0

BVces	Collector to Emitter Breakdown	Ic = 10 mA	40			Volts
BVebo	Emitter to Base Breakdown	Ie = 5 mA	3.5			Volts
Hfe	Current Gain	Vce = 5V, $Ic = 200 mA$	20		120	
Cob	Output Capacitance	Vcb = 24 F = 1 MHz		7		pF
θјс	Thermal Resistance	$Tc = 25^{\circ}C$			17.0	°C/W

Initial Issue July, 1994


GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHZ RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.





DIM	INCHES
Α	.475
В	.150
С	.053
D	.100
Е	.250
F	.245
G	.555
Н	.600
1	.180
J	.053
K	.525
L	.240
М	.100
Ν	.265
0	.100

2225-4L TEST CIRCUIT



DIELECTRIC = 20 MIL THICK TFE Er = 2.43 C1, C2 = 62pF CHIP ATC "B" C3 = 10 MFD @ 35V RFC = 4 turns #22 wire 1/16" I.D.



CAGE	DWG NO.			REV
OPJR2		2225-4L		A
	SCALE	1/1	SHEET	